

# DECT Handset G277

Compact and professional handset for mobile office users



The DECT handset G277 is an entry level professional mobile handset providing a range of mobile unified communication features, plug and play installation, charger compatibility and more for effective operation in various businesses.

## Main Product Features

- > Many different call control features seamlessly integrated with the PBX
- > Providing staff the freedom to work at any place and freely move around
- > Valuable unified communications, including central directory access and presence
- > Intuitive colour user interface and icon based menus
- > Single or dual charger for additional battery charging and compatible with previous generation chargers
- > Freedom, comfort and flexibility with options like headset and built-in trembler
- > DECT compliance for superior quality speech and security
- > High-definition audio

## At a glance

- > Appealing design, lightweight and slim-line
- > Bright 1.8-inch colour display
- > Rugged belt clip
- > Central Directory and Presence
- > Loudspeaker and handsfree mode
- > Simple plug-and-play with MicroSD card
- > Very long battery life and standby time
- > USB-C interface for headset



## Features G277

<b>Call handling <sup>1)</sup></b>	Automatic call answer	Call reject option
	Caller log	HD audio and seamless handover
	CLI (name and number support)	On-hook number preparation
	Last number redial	Silent Charging
	Recall/hold (enquiry)	Talk time up to 20 hours
	Standby time up to 160 hours	
<b>Design</b>	Robust design for use in professional environments	Dust and water resistance: IP40
	Triple colour LED indication for e.g. missed call and MWI	HAC compliant
<b>Directory</b>	Corporate directory	Personal phone book with multiple numbers per contact
<b>Display</b>	Color graphic 1.77 TFT display, 128 x 160 px (65K)	Date & time indication: synchronized with PBX clock
	Illuminate display on incoming calls	Character set: WideChar (UTF-16)
	Power saving mode: display dim lit or completely off	LCD Backlit
<b>Headset</b>	Wired headset support (USB-C)	
<b>Keys</b>	12 keypad keys (0..9, *, #) with text mode support	On- and off-hook: 2 separate keys
	Recall (enquiry) key combined with on-hook key	Power on/off key combined with off-hook key
	Menu navigation keys: up, down, left and right and OK	Soft keys: 3, menu dependent function
	Speakerphone key	Increase and decrease volume
		Menu key
<b>Localization</b>	Supported languages: 14	Multiple (RF) power levels
	Triple frequency band	
<b>Memory card (optional)</b>	Storage of configuration and subscription data personal phone book and caller filte	Easy subscription transfer to another handset via memory card programming
	Easy (pre-)installation via memory card programming	Memory card type: MicroSD
	Blocking of changes to the configuration settin	
<b>Menu</b>	Easy menu programming	
<b>Mobility</b>	Antenna diversity	Multiple subscriptions DECT systems: 10
<b>Other features</b>	Automatic key lock	
<b>Sound/Audio</b>	Adjustable ringer volume	Adjustable earpiece/loudspeaker volume
	Loudspeaker mode/hands free	Microphone mute
	Trembler	Silent ring support
<b>Security</b>	Automatic encryption for secure calls	
<b>Service/Maintenance</b>	Software upgrading via air interface <sup>2)</sup>	Backup of local data via memory card
	Software upgrading via headset connector (USB-C)	5-year life cycle
<b>User data</b>	Internal memory to store configuration data, personal phone book, messages, caller log, caller filter and calendar entries	Optional memory card
<b>User interface</b>	Icon driven menu	Status line indicators in the display
	Configurable LED (3-col) indicator for e.g. missed call and message waiting	Distinctive melodies for external and internal calls, messages and priorities and per phonebook contact
	Ringer tones/melodies: 20	Audible indicators are user selectable
	Selectable display background	

1) Features depend on the capabilities of the PBX and the DECT system used

2) Needs to be supported by the DECT systems

## Physical Characteristics G277

<b>Dimensions</b>	Handset: 128 x 49 x 21 mm	
	Charger: 60 x 60 x 30 mm	
	Charger Rack: 462 x 77 x 61 mm	
<b>Weight</b>	Handset: 130 g	
	Charger: 60 g	
	AC Adapter: 25 g	
<b>Protection</b>	Handset: IP40	
<b>Range</b>	Indoor: 50 m max <sup>3)</sup>	
	Outdoor: 300 m max <sup>4)</sup>	
<b>Power Supply</b>	Handset: 3.7V, 1100mAh Lithium-ion battery	
	Charger (EU mains plug, USB output)	
	Input: 100-240VAC/50/60Hz/250mA	
	Output: 5VDC/1000mA	
	Charger (UK, US, AU mains plug, USB output) <sup>4)</sup>	
	Input: 100-240VAC/50/60Hz/125mA	
	Output: 5VDC/900mA	
<b>Colour and finishin</b>	Handset: Black	
	Desktop charger: Black	
	Charger rack: Black	
<b>Audible indicators</b>	Key click	Charger warning
	Coverage warning	Confirmation ton
<b>Status display line indicators</b>	Battery condition	Message waiting
	Field strength	Microphone mute
	Key lock active	Missed call
	Loudspeaker active	Ringer off
<b>LED indicators</b> Three indicators can be assigned to the indicator LED	Battery low	Voice message
	Missed call	Silent charging
<b>Supported menu languages</b>	Danish, Dutch, English, French, German, Greek, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish	

<sup>3)</sup> Radio coverage depends on environment and presence of obstacles

<sup>4)</sup> The mains plug contains a changeable part for the different power plugs

## Transmission & Frequency

<b>Transmitted radio RF power</b>	Less than 250 mW <sup>5)</sup>
<b>Average Radio RF power</b>	10mW
<b>Frequency band EMEA</b>	1880 – 1900 MHz
<b>Frequency band Thailand <sup>6)</sup></b>	1900 – 1906 MHz
<b>Frequency band Latin America <sup>6)</sup></b>	1910 – 1930 MHz
<b>Frequency band North America <sup>6)</sup></b>	1920 – 1930 MHz

<sup>5)</sup> The transmitted Radio RF power is according to local regulations

<sup>6)</sup> The G277 handset has a triple frequency band and can be used in the EMEA, American and Thai DECT frequency band

## Environmental Conditions

<b>Temperature range</b>	<b>Relative Humidity</b>
Operating: -15°C to +55°C	Operating: 10 to 93%
Charging: +5°C to +45°C	Transport: 10 to 95%
Storage: -20°C to +60°C	Storage: 10 to 93%
Transport: -30°C to +60°C	

## Compliance

<b>EMC</b>	EN 301 489-1, EN 301 489-6
<b>EMF</b>	EN 50663, EN 62479
<b>RF</b>	EN 301 406
<b>SAR</b>	EN 61000-4-2, EN 61000-4-3
<b>Safety</b>	EN 62368-1

## Compatibility

<b>Platform Compatibility</b>	All NEC Communication Platforms 7)
	Certified SIP enabled PBXs or SIP server
	Alcatel Lucent, Avaya, Cisco and Broadsoft certified system

7) SL Series, SV8xxx, SV9xxx, iS3000/SIP@Net, 3C

## Directives & Regulations

<b>EMC</b>	2014/30/EU - Electromagnetic Compatibility
<b>LVD</b>	2014/35/EU - Low Voltage Directive
<b>RED</b>	2014/53/EU - Radio Equipment Directive
<b>RoHS</b>	2011/65/EU - Restriction of the use of certain hazardous substances in EEE
<b>WEEE</b>	2012/19/EU - Waste Electrical and Electronic Equipment
<b>ERP</b>	2009/125/EC - Eco-design requirements for Energy-related Products (ErP)

## Accessories

<b>G277 accessories</b>	Swivel belt clip attachment and belt clip
	Spring Belt Clip
	USB-C to 3.5 mm conversion cable
	Vertical pouch (swivel belt-clip, handset can be used while in pouch)
	Battery pack
	Desktop charger with/without spare battery charger and AC adapter
	Charger rack (6 handsets) with AC adapter

## Package content

G277 handset with belt clip

<b>G277 package content</b>	G277 handset with belt clip
	Lithium-ion battery pack

DECT Handset G277



Gx77 desktop charger and spare battery desktop charger



USB-C to 3.5 mm conversion cable



Charger rack (6 handsets) with AC adapter



G277 at various angles

For further information please contact your local NEC representative or:

**Corporate Headquarters (Japan)**  
NEC Corporation  
[www.nec.com](http://www.nec.com)

**Asia Pacific**  
NEC Asia Pacific  
[www.nec.com.sg](http://www.nec.com.sg)

**EMEA (Europe, Middle East, Africa)**  
NEC Europe  
[www.nec-enterprise.com](http://www.nec-enterprise.com)

**North Americas (USA, Canada)**  
NEC Corporation of America  
[www.necam.com](http://www.necam.com)

**Latin Americas (Brazil)**  
NEC Latin America  
[br.nec.com](http://br.nec.com)